


# 77095

## CABLE PARA ALARMA DE INCENDIO 2X18 AWG FPLR COLOR ROJO 305 METROS

Fire Alarm PVC Unshielded Cables 22 Thru 12AWG "Footage marked 0Ft thru 500Ft or 1000Ft" ETL or UL Listed FPLR, California Fire Marshall Approved Application: Fire Alarm, Smoke Detectors, Strobes and Low Voltage AC Power



UPG No.	Description	Compound:		Non-Shielded or Shielded	Multi-Cond. Part, Zip, or Combo	Conductors		Stranded or Solid	Color	Put-Up	Length	Nom. O.D.	Copper Wt. per Unit
		PVC, Plenum, Direct Burial	NEC Article			Count	AWG						
77249	UF2204S-2C5	PVC	FPLR	NS	Multi-Cond	4	22	SOL	Red	Coil Pack	500	0.1240	3.8600
77250	UF2204S-9C5	PVC	FPLR	NS	Multi-Cond	4	22	SOL	White	Coil Pack	500	0.1240	3.8600
77093	UF2204S-2B1	PVC	FPLR	NS	Multi-Cond	4	22	SOL	Red	Box	1000	0.1240	7.7200
77094	UF1802S-2B5	PVC	FPLR	NS	Multi-Cond	2	18	SOL	Red	Box	500	0.1360	4.9023
77095	UF1802S-2B1	PVC	FPLR	NS	Multi-Cond	2	18	SOL	Red	Box	1000	0.1360	9.8045
77553	UF1802S-2S1	PVC	FPLR	NS	Multi-Cond	2	18	SOL	Red	Spool	1000	0.1360	9.8045
77096	UF1802S-9B1	PVC	FPLR	NS	Multi-Cond	2	18	SOL	White	Box	1000	0.1360	9.8045
77531	UF1802-9C5	PVC	FPLR	NS	Multi-Cond	2	18	SOL	White	Coil	500	0.1360	4.9023
77097	UF1804S-2B5	PVC	FPLR	NS	Multi-Cond	4	18	SOL	Red	Box	500	0.1720	9.8045
77098	UF1804S-2B1	PVC	FPLR	NS	Multi-Cond	4	18	SOL	Red	Box	1000	0.1720	19.6090
77417	UF1804S-2S1	PVC	FPLR	NS	Multi-Cond	4	18	SOL	Red	Box	1000	0.1720	19.6090
77099	UF1804S-9B1	PVC	FPLR	NS	Multi-Cond	4	18	SOL	White	Box	1000	0.1720	19.6090
77533	UF1804S-9B5	PVC	FPLR	NS	Multi-Cond	4	18	SOL	White	Box	500	0.1720	9.8045
77100	UF1804S-2B1	PVC	FPLR	NS	Multi-Cond	6	18	SOL	Red	Box	1000	0.1920	29.4135
77251	UF1602S-2B5	PVC	FPLR	NS	Multi-Cond	2	16	SOL	Red	Box	500	0.1560	7.7200
77101	UF1602S-2B1	PVC	FPLR	NS	Multi-Cond	2	16	SOL	Red	Box	1000	0.1560	15.4399
77418	UF1602S-2S1	PVC	FPLR	NS	Multi-Cond	2	16	SOL	Red	Spool	1000	0.1560	15.4399
77423	UF1602S-3B1	PVC	FPLR	NS	Multi-Cond	2	16	SOL	Orange	Box	1000	0.1560	15.4399
77424	UF1602S-4B1	PVC	FPLR	NS	Multi-Cond	2	16	SOL	Yellow	Box	1000	0.1560	15.4399
77425	UF1602S-5B1	PVC	FPLR	NS	Multi-Cond	2	16	SOL	Green	Box	1000	0.1560	15.4399
77426	UF1602S-6B1	PVC	FPLR	NS	Multi-Cond	2	16	SOL	Blue	Box	1000	0.1560	15.4399
77427	UF1602S-9B1	PVC	FPLR	NS	Multi-Cond	2	16	SOL	White	Box	1000	0.1560	15.4399
77253	UF1604S-2S1	PVC	FPLR	NS	Multi-Cond	4	16	SOL	Red	Spool	1000	0.1820	30.8799
77374	UF1604S-2B5	PVC	FPLR	NS	Multi-Cond	4	16	SOL	Red	Box	500	0.1820	15.4400
77372	UF1402S-2B5	PVC	FPLR	NS	Multi-Cond	2	14	SOL	Red	Box	500	0.1820	12.5200
77102	UF1402S-2B1	PVC	FPLR	NS	Multi-Cond	2	14	SOL	Red	Box	1000	0.1820	25.0381
77419	UF1402S-2S1	PVC	FPLR	NS	Multi-Cond	2	14	SOL	Red	Spool	1000	0.1820	25.0381
77428	UF1402S-3B1	PVC	FPLR	NS	Multi-Cond	2	14	SOL	Orange	Box	1000	0.1820	25.0381
77429	UF1402S-4B1	PVC	FPLR	NS	Multi-Cond	2	14	SOL	Yellow	Box	1000	0.1820	25.0381
77430	UF1402S-5B1	PVC	FPLR	NS	Multi-Cond	2	14	SOL	Blue	Box	1000	0.1820	25.0381
77392	UF1402S-9B1	PVC	FPLR	NS	Multi-Cond	2	14	SOL	White	Box	1000	0.1820	25.0381
77254	UF1404S-2S1	PVC	FPLR	NS	Multi-Cond	4	14	SOL	Red	Spool	1000	0.2160	50.0762
77103	UF1202S-2S1	PVC	FPLR	NS	Multi-Cond	2	12	SOL	Red	Spool	1000	0.2160	39.6035
77255	UF1202S-2B1	PVC	FPLR	NS	Multi-Cond	2	12	SOL	Red	Box	1000	0.2160	39.6035

Fire Alarm Stranded Suitable for Direct Burial/Wet Locations PVC Unshielded Cables 22 thru 12AWG "Footage marked 0Ft thru 500Ft or 1000Ft" ETL or UL Listed FPLR or PLTC, California Fire Marshall Approved Application: Fire Alarm, Smoke Detectors, Strobes and Low Voltage AC Power